

Solid Cushion Tires



Key Specifications

Tire Size	Tread Pattern	Cushion Rows	S.W.	Tread Depth	Outer Diameter	Rim Size	Weight (lbs)	Load Capacity (lbs)**
19X8-12	DT	1	7.1"	1.0"	19.1"	8"x12"	83	2,640
23X5.7-12	DT	2	5.7"	1.7"	22.4"	4"x12"	87	2,860-3,440
23X8.5-12	DT	2	7.5"	1.7"	22.8"	5"x12"	101	3,750-4,500
27X8.5-15	DT	2	7.9"	2.0"	26.6"	5.5"x15"	143	4,630-5,555
30X10-16	DT	4	9.3"	1.6"	30.3"	6"x16"	197	4,840
30X10-16	AT	4	9.0"	1.6"	30.0"	6"x16"	217	4,840
30X8.5-16	DT	2	7.9"	1.9"	30.0"	6"x16"	175	4,410-5,290
30X10-20	DT	2	9.0"	1.5"	31.8"	7"x20"	233	6,600
32.5X15-16	DT	2	14.7"	2.3"	32.3"	11.25"x16"	347	7,930-9,520
33X12-16	DT	2	11.3"	3.4"	32.3"	8"x16"	271	7,050-8,460
33X12-20	DT	2	10.8"	1.5"	33.0"	7.5"x20"	270	7,700
33X12-16	AT	4	10.2"	1.9"	30.2"	8"x16"	300	8,270
36.5X14-20	DT	2	13.5"	2.0"	36.0"	11"x20"	437	10,580
36.5X12-20	DT	2	11.8"	3.1"	36.8"	8"x20"	368	7,937
38.5X14-20*	DT	2	13.5"	2.4"	38.1"	11"x20"	377	9,260-11,110
18.0-20	DT	2	16.6"	4.1"	41.7"	12"x20"	386	17,630-21,160
385/65-24	DT	2	14.2"	2.0"	41.7"	10"x24"	611	17,630-21,160
385/70-20	DT	2	14.2"	2.0"	41.7"	10"x20"	688	14,330-17,190
50x16-24*	AT	2	15.8"	3.1"	49.2"	11.5"	855	17,630-21,160
50X13-24	AT	2	12.6"	3.4"	49.2"	8.5"x24"	842	14,990-17,990
15.5-25	DT	2	15.2"	3.7"	50.0"	11.25"x25"	1,043	17,190-20,630
50X13-24	DT	2	12.6"	4.2"	50.0"	8.5"x24"	778	14,990-17,990
53X14-24	AT	2	13.4"	3.5"	52.0"	8.5"x24"/10"x24"	979	17,630-21,160
17.5-25	DT	2	17.3"	4.9"	52.8"	14"x25"	1,250	18,740-22,480
17.5-25	AT	2	17.3"	5.8"	52.8"	14"x25"	1,365	20,940-25,130
17.5-25	SS	2	17.3"	-	52.8"	14"x25"	1,398	20,940-25,130
53X14-24	DT	3	13.4"	4.5"	52.8"	8.5"x24"/10"x24"	974	18,740-21,160
53X14-24	RT	2	14.2"	4.7"	53.1"	8.5"x24"/10"x24"	1,008	17,630-21,160
20.5-25	AT	2/3	20.5"	3.7"	58.3"	17"x25"	1,863	23,150-27,780
20.5-25	SS	2	20.5"	-	59.1"	17"x25"	1,929	23,150-27,780
16.00-25*	AT	2	16.1"	3.8"	59.1"	11.25"	1,411	22,040-26,450
23.5-25	AT	2/3	23.2"	7.5"	63.4"	19.5"x25"	2,661	28,660-34,390
23.5-25	SS	2	23.2"	-	63.4"	19.5"x25"	2,698	28,660-34,390
18.0-25*	RT	2	19.3"	3.3"	63.6"	13"x25"	1,874	26,450-31,740
18.0-25*	SS	2	18.1"	-	63.4"	13"x25"	1,874	26,450-31,740
23.5-25	DT	2	22.8"	7.5"	63.8"	19.5"x25"	2,491	26,450-31,740
26.5-25*	AT	2/3	25.6"	8.4"	67.7"	22"x25"	2,965	35,270-42,330
26.5-25*	SS	2	25.6"	-	67.7"	22"x25"	3,042	35,270-42,330
26.5-25*	DT	2	26.4"	8.4"	68.9"	22"x25"	2,983	31,970-38,360
29.5-25*	AT	2	39.1"	7.9"	73.6"	25"x25"	4,090	40,790-48,940
35/65-33*	AT	2	33.5"	7.8"	79.9"	28"x33"	5,203	52,910-63,490

Weight may vary based on custom rim specifications; The above specifications are provided for reference only and may change without notice.

* Rimless Tire - if customer provides Measurement sheet, McLaren can search for rim option and produce it.

** Load Capacity will vary based on machine speed (15 m/h - 3.5 m/h)